______ MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. ______ PRODUCT NUMBER: 534 IDENTITY: MR. MECHANIC Revision Date: 01/18/2007 ______ Section I ______ Manufacturer's Name: OUEST CHEMICAL CORPORATION Telephone Numbers: 12255 FM 529 Emergency: NORTHWOODS INDUSTRIAL PARK 800/255-3924 Information: HOUSTON State: TX Zip Code:77041 713/8968188 ______ HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 1 PERSONAL PROTECT: A Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.) ______ Name Cas No. OSHA PEL ACGIH TLV OTHER LIM % ETHYL ACETATE 141-78-6 400 PPM 400 PPM ISOPARAFINIC HYDROCARBON 64742-47-8 400 PPM 400 PPM 64741-44-2 5 MG/M3 5 MG/M3 N/A MINERAL SEAL OIL PETROLEUM DISTILLATES 64742-54-7 5 MG/M3 10 MG/M3 N/A 68476-86-8 1000 PPM 600 PPM N/A PROPANE/N-BUTANE Section III: PHYSICAL/CHEMICAL CHARACTERISTICS ______ Boiling Point: 180 Specific Gravity (water=1) 0.83 Vapor Pressure (mm Hg) 30 Melting Point:
Vapor Density (AIR=1) >1 Evaporation Rate:
Solubility in Water: 0% (Butyl Acetate=1) Melting Point: Evaporation Rate: N/A <1 Appearance and Odor: THIN BROWN LIQUID WITH STRONG SOLVENT ODOR. Section IV: FIRE AND EXPLOSION HAZARD DATA ______

Flash Point(Method Used):+110F TCC Flammable Limits: LEL:N/A UEL: N/A

Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER

Special Fire Fighting Procedures: SELF CONTAINED BREATHING APPRATUS.

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

PRODUCT NUMBER: 534 ______

Stability: Unstable: Conditions to avoid:

Stable: X TEMPERATURES ABOVE 120 F

Incompatability (Materials to Avoid): MAY AFFECT CERTAIN PLASTICS

Hazardous Decomposition or Byproducts: OXIDES OF CARBON.

Hazardous Polymerization: May Occur: Will Not Occur: X

Conditions to Avoid: NONE KNOWN

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Health Hazards (Acute and Chronic):

INHALATION: DIZZINESS. PROLONGED EXPOSURE MAY LEAD TO UNCONSCIOUSNESS.

EYES: STRONG IRRITATION. SKIN: MILD IRRITATION. MAY CAUSE LOCALIZED

DEFATTING. INGESTION: MAY CAUSE NAUSEA AND/OR VOMITTING.

Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Req:Yes

Signs and Symptoms of Exposure: SEE HEALTH HAZARDS

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. CONSULT PHYSICIAN. EYES: FLUSH WITH WATER FOR 15 MINUTES. CONSULT PHYSICIAN IS IRRITATION PERSISTS. SKIN: WASH WITH SOAP AND WATER. CONSULT PHYSICIAN IF IRRITATION PERSISTS. INGESTION: CONSULT PHYSICIAN IMMEDIATELY.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP WITH RAG OR USE SOME ABSORBENT CLAY MATERIAL.

Waste Disposal Method: DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GUIDELINES. DO NOT REUSE EMPTY CONTAINER. DO NOT PUNCTURE OR INCINERATE CONTAINER. WRAP CONTAINER AND PLACE IN TRASH COLLECTION.

Precautions to be Taken in Handling and Storing: DO NOT USE OR STORE NEAR HEAT OR OPEN FLAME. EXPOSURE TO TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Other Precautions: N/A

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN WELL VENTILATED AREA

Ventilation: Local Exhaust:ADEQUATE

Mechanical: N/A Special: N/A

Other: N/A Protective Gloves: N/A

Eye Protection: SAFTEY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED.

Other Protective Clothing or Equipment:

Work/Hygienic Practices:

WASH HANDS AFTER USE.