MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

PRODUCT NUMBER: 570 IDENTITY: QUIK-ZINC

IDENTITY: QUIK-ZINC Revision Date: 01/21/2007

Section I

Manufacturer's Name:QUEST CHEMICAL CORPORATION Telephone Numbers: Address: 12255 FM 529 Emergency: NORTHWOODS INDUSTRIAL PARK 800/255-3924 HOUSTON Information: State: TX Zip Code:77041 713/8968188

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 3 HEALTH: 1 PERSONAL PROTECT: A

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

Name	Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	olo
ACETONE PROPANE/N-BUTANE XYLENE(XYLOL) * ZINC DUST *	67-64-1 68476-86-8 1330-20-7 7440-66-6	100 PPM	750 PPM 600 PPM 100 PPM 10 MG/M3	N/A N/A N/A	

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:	165	Specific Gravity (water=1)	1.20		
Vapor Pressure(mm Hg)	100	Melting Point:	N/A		
Vapor Density(AIR=1)	1	Evaporation Rate:	<6		
Solubility in Water:	0%	(Butyl Acetate=1)			
Appearance and Odor: GRA	Y WITH A	AROMATIC SOLVENT ODOR			

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used):65F TCC Flammable Limits: LEL:N/A UEL: N/A Extinguishing Media: STANDARD CHEMICAL FIRE EXTINGUISHER Special Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS

Unusual Fire and Explosion Hazards: WARNING: FLAMMABLE. CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO TEMPERATURES ABOVE 120F, OR MAY CAUSE BURST-ING. MAY DEVELOP A FLAMMABLE ATMOSPHERE IN CONFINED AREAS.

Section V: REACTIVITY DATA

PRODUCT NUMBER: 570

Stability: Unstable:Conditions to avoid: TEMPERATURES ABOVEStable:X120 F. HOT SURFACESIncompatability (Materials to Avoid): STRONG OXIDIZERS

Hazardous Decomposition or Byproducts: EXPOSURE TO RED HOT SURFACES MAY PRODUCE OXIDES OF CARBON AND NITROGEN. Hazardous Polymerization: May Occur: Will Not Occur: X Conditions to Avoid: NONE

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion:YES Health Hazards(Acute and Chronic): INHALATION: DIZZINESS, NAUSEA. SKIN: LOCALIZED DEFATTING OF SKIN. SENSITIVE SKIN MAY BREAK OUT IN TO RASH. INGESTION: WILL CAUSE NAUSEA, SICKNESS. EYES: MAY CAUSE IRRITATION OR A BURNING SENSATION. Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO Signs and Symptoms of Exposure: SEE HEALTH HAZARDS.

Medical Conditions Generally Aggravated by Exposure: NONE KNOWN

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR. CONSULT PHYSICIAN IF DIFFICULTY IN BREATHING PERSISTS. EYES: FLUSH WITH WATER FOR 15 MINUTES. CONSULT PHYSICIAN IF IRRITATION PERSISTS. SKIN: WASH WITH SOAP AND WATER.INGESTION: DO NO INDUCE VOMITING. CONSULT PHYSICIAN.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: CONTAIN SPILL AND WIPE UP WITH A RAG. SPILLED RESIDUE SHOULD BE CLEANED UP WITH SOLVENT.

Waste Disposal Method: RESIDUE SHOULD BE KEPT IN TIGHTLY SEALED CONTAINERS AND DISPOSED OF IN ACCORDANCE WITH FEDERAL, STATE OR LOCAL GUIDELINES.

Precautions to be Taken in Handling and Storing: KEEP AWAY FROM HEAT OR OPEN FLAME. STORE IN A COOL DRY AREA. EXPOSURE TO TEMPERATURES >120 F MAY CAUSE BURSTING.

Other Precautions: VAPOR MAY COLLECT IN LOW LYING AREAS.

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN WELL VENTILATED AREAS. Ventilation: Local Exhaust:SUFFICIENT Mechanical: N/A Special: N/A Other: N/A Protective Gloves:N/A Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED. Other Protective Clothing or Equipment: ADEQUATE TO PROTECT EXPOSED SKIN. Work/Hygienic Practices: WASH HANDS THOROUGHLY WITH SOAP AND WATER AFTER USE.