MATERIAL SAFETY DATA SHEET (SUBSTITUTES FOR OSHA FORM 174): May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200.

PRODUCT NUMBER: 596 IDENTITY: REVIVE RUST CONVERTER Revision Date: 01/21/2007 Section I

Manufacturer's Name	:QUEST CHEMICAL CORPORATION	Telephone Numbers:
Address:	12255 FM 529	Emergency:
NORTHWOODS INDUSTRIAL PARK HOUSTON		800/255-3924
		Information:
	State: TX Zip Code:77041	713/8968188

HMIS CODES: REACTIVITY: 1 FLAMMABILITY: 4 HEALTH: 2 PERSONAL PROTECT: B

Section II: HAZARDOUS INGREDIENTS/IDENTITY INFORMATION (All of the ingredients contained in this product are listed on the TSCA inventory.)

Name		Cas No.	OSHA PEL	ACGIH TLV	OTHER LIM	olo
ACETONE ETHYLENE GLYCOL ISOPROPYL ALCOHOL PROPANE/N-BUTANE	*	67-64-1 107211 67-63-0 68476-86-8	1000 PPM N/A 400 PPM 1000 PPM	750 PPM 100 MG/M3 400 PPM 600 PPM	N/A N/A N/A 	

Comment:

THIS PRODUCT CONTAINS THE TOXIC CHEMICALS MARKED WITH AN * SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF THE EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT OF 1986 AND OF 40CFR372.

Section III: PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:	N/D	Specific Gravity (water=1)	0.79
Vapor Pressure(mm Hg)	N/D	Melting Point:	N/D
Vapor Density(AIR=1)	>1	Evaporation Rate:	>1
Solubility in Water:	100%	(Butyl Acetate=1)	
Appearance and Odor:	CLEAR BROWN S	SPRAY, SOLVENT ODOR.	

Section IV: FIRE AND EXPLOSION HAZARD DATA

Flash Point(Method Used): OF TCC Flammable Limits: LEL:3.5 UEL: 8.0 Extinguishing Media: STANDARD DRY CHEMICAL FIRE EXTINGUISHER Special Fire Fighting Procedures: WEAR SELF CONTAINED BREATHING APPARATUS.

Unusual Fire and Explosion Hazards: FLAMMABLE. CONTENTS UNDER PRESSURE. DO NOT PUNCTURE OR INCINERATE CONTAINER. KEEP AWAY FROM HEAT OR TEMPERATURES ABOVE 120 F. EXPOSURE TO TEMPERATURES ABOVE 120F MAY CAUSE CAN TO BURST.

PRODUCT NUMBER: 596

Stability: Unstable:Conditions to avoid:
TEMPERATURES ABOVE 120FIncompatability (Materials to Avoid): AVOID ALKALIS AND STRONG OXIDIZERS.KEEP AWAY FROM HEAT AND OPEN FLAME.Hazardous Decomposition or Byproducts: CARBON MONOXIDE, CARBON DIOXIDE.

Hazardous Polymerization: May Occur: Will Not Occur: X Conditions to Avoid: N/A

Section VI: HEALTH HAZARD DATA

Routes of Entry: Inhalation: YES Skin: YES Ingestion:YES Health Hazards(Acute and Chronic): EYES: SEVERE IRRITATION OR BURNING. SKIN: SEVERE IRRITATION, LOCALIZED DEFATTING. INHALATION: SEVERE IRRITATION TO EYES, NOSE AND RESPIRATORY TRACT. INGESTION: NAUSEA, STOMACH UPSET, VOMITING. Carcinogenicity: NTP:NO IARC Monographs:NO OSHA Reg:NO Signs and Symptoms of Exposure: SEE HEALTH HAZARDS ABOVE

Medical Conditions Generally Aggravated by Exposure: EXCESSIVE EXPOSURE WILL AGGRAVATE RESPIRATORY, CARDIOVASCULAR OR PULMONARY ILLNESSES.

Emergency and First Aid Procedures: INHALATION: REMOVE TO FRESH AIR.CONSULT PHYSICIAN IF DIFFICULTY IN BREATHING PERSISTS. EYES: FLUSH WITH WATER FOR 15 MINUTES. CONSULT PHYSICIAN. SKIN: WASH AREA WITH SOAP AND WATER. INGESTION: CONSULT PHYSICAN.

Section VII: PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: WIPE UP SMALL SPILL WITH TOWEL AND ALLOW AREA TO DRY. EXCESS MAY BE REMOVED AFTER DRYING WITH SANDPAPER OR OTHER SCRAPING DEVICE. DISPOSE OF RESIDUE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL GUIDELINES. Waste Disposal Method: WRAP CONTAINER AND PLACE IN TRASH COLLECTION. DO NOT PUNCTURE OR INCINERATE CONTAINER.

Precautions to be Taken in Handling and Storing: STORE IN A COOL DRY AREA. KEEP AWAY FROM HEAT OR OPEN FLAMES.

Other Precautions: TEMPERATURES ABOVE 120 F MAY CAUSE BURSTING.

Section VIII: CONTROL MEASURES

Respiratory Protection: USE ONLY IN A WELL VENTILATED AREA. Ventilation: Local Exhaust:ADEQUATE Mechanical: N/A Special: N/A Other: N/A Protective Gloves:CHEMICAL RESISTANT Eye Protection: SAFETY GLASSES ARE RECOMMENDED WHENEVER CHEMICALS ARE USED. Other Protective Clothing or Equipment: IF EXPOSURE LIMITS ARE EXCEEDED WEAR A NIOSH APPROVED RESPIRATOR. Work/Hygienic Practices: WASH HANDS AFTER USE.